



# Drum melter GX21 FlexControl

Heated drum melter with innovative "FlexControl" system, automated air relief and seamless plate-seal to process hotmelt-adhesives and sealants from 20 kg / 5 Gal. hobbos with volumetric metering pump rates



The equipment concept based on pneumatic pressure cylinders and an anti-stick-coated melting plate with a gearpump in configurable variations, ensures low maintenance issues during melting and metering of suitable thermoplastics or reaktive adhesives and sealants. Best operator safety will be achieved related to dedicated process step monitoring and a two-hand-operation



Melting plate with front side deaeration module



Pneumatic control



Start screen of the FlexControl system



Drum melter GX21 with PLC Siemens Profinet interface, touchscreen control panel and signal light

SM Klebetechnik Vertriebs GmbH  
Otto-Hahn-Str. 19a  
D-52525 Heinsberg

Phone: +49 (0) 24 52 / 91 72-0  
Fax: +49 (0) 24 52 / 91 72-20  
E-Mail: [info@sm-klebetechnik.de](mailto:info@sm-klebetechnik.de)

[www.sm-klebetechnik.de](http://www.sm-klebetechnik.de)

Delivery and services are effected in accordance with the current terms of business of the SM Klebetechnik Vertriebs GmbH.

## Standard equipment

- FlexControl - new and innovative microprocessor control unit of SM Klebetechnik
- Dosing meter - automatic speed control - quantity specification g/m<sup>2</sup> g/lfdm.
- Pressure sensor with PL "c" instead of bypass - unique for this device category!
- Colour display and touch panel control unit - intuitive system operation
- Weekly timer, operating hour counter, recipe menu, user + password
- Remote control via tablet or smartphone
- Software update via USB interface/storage of recipes on a USB stick
- Temperature setback can be activated automatically or manually
- PID temperature controller with self-tuning for sensor PT100, Ni120, NTC
- Seamless plate seal (PTFE encapsulated silicone gasket ring)
- Precision gear pump for volumetric delivery
- Automatic start-up protection of the pump / maintenance-free three-phase drive
- Automatic 100% venting of the underside of the panel and pump

## Optional equipment

- Possible engineered system design
- Electronic pressure control with mechanical over-pressure relief
- Process data logging
- Precise liquid level reading with programmable threshold switch function
- Ventilation hood, drum jacket, drum pre-heating etc.
- Material flow meter and/or material temperature reading
- Different melting plate configurations available
- Alternative pump sizes available
- Compatible connection with systems from other manufacturers available
- Heated buffertank unit with extended piston reservoir (first in - first out) for no downtime at drum change

## Technical data

Heating:	electrical
Wattage:	5 KW
Melt capacity:	5 - 25 kg/h (depends on medium)
Voltage:	3/N/PE 400 V AC, 50 Hz
Pump system:	gear pump
Pump rate:	5 kg/h – 40 kg/h
Pump drive:	3-phase brush-less AC Motor
Drive power:	250 W
Speed control:	Frequency converter
Hose connections:	1
Dimensions L, W, H [mm]:	1400 x 510 x 1950